



#### DESCRIPTION

Indoor matt plastic paint with good opacity and whiteness. It can be used outdoors if the climatological conditions are mild.

#### RECOMMENDED USE

Plastic paint for all types of masonry surfaces (plaster, stucco, cement, etc.), indoor decoration of walls and ceilings, plasterboard panels and all construction materials when desired to achieve a low cost. Smooth finishes due to an easy application and retouch. It can be used outdoors if the climatological conditions are mild.

#### CHARACTERISTICS

- . Good resistance, hardness and adhesion.
- . Mould resistant. It prevents mould and algae stains.
- . Excellent performance.
- . Low-cost. Good whiteness.
- . Soft appearance and touch.
- . Protection from humidity.
- . Good brush stroke, coverage and yield.
- . Best value for money.
- . Wet scrub resistant.

#### TECHNICAL CHARACTERISTICS

Main component:	Acrylic copolymers in aqueous dispersion.
Pigments:	Titanium dioxide and additives.
Appearance:	Matt.
Diluent:	Water.
Solids by weight:	67 ± 2 %
Specific weight:	1,66 ± 0,05 g/ml
Wet scrub resistance:	Type I (UNE 48243).
Volatile organic compounds (2010):	Maximum 30 g/l
Colour:	White. For other colours, please consult us.
Drying at 20°C:	30-40 minutes.
Repainting at 20°C:	Minimum 4- 6 hours.
Theoretical yield:	6-8 m <sup>2</sup> /l and coat. Depending on the irregularity and absorption of the surface.
Packaging:	4L and 14 L



# TECHNICAL DATASHEET

## K-15

Indoor and outdoor matt plastic paint

### **APPLICATION**

#### **Surface preparation:**

On new construction material surfaces, it is advisable to check if their state is adequate. Clean the surface to remove any dust remains, grease and general dirt and apply the first coat diluted between at least 10-15 % with water. In order to consolidate or unify the absorption, it is recommendable to use an acrylic binder like our BINDER to achieve a better result.

On already painted surfaces, if the paint is in a bad state, it must be removed. In case of dealing with distemper paste, proceed like if it were a new surface. If it has good adhesion, sand it softly to tinge and remove the dust before painting.

In case of efflorescence or salty residue, treat it with any neutralizer liquid or hydrochloric acid at 10 % in water and rinse with plenty of water and let it dry before painting.

In case of pollution due to mould, fungus, algae or other elements, apply a water and bleach solution or hydrochloric acid at 10 % on the surface and leave it for approximately 15-20 min. Next, rinse with plenty of water and let it dry completely before applying the paint. Proceed like if it were a new surface or an already painted surface.

To paint other surfaces not specified in this technical datasheet, please contact our Technical Department.

#### **Instructions:**

Stir the content until it is uniform. Always apply on clean, dry surfaces without any dust, wax, grease, etc. It can be applied with brush, roller or spray gun. For brush and roller application, apply the first coat diluted between 10-15 % with water and the second one diluted lightly. For spray gun application, dilute it between 5-10 %.

Never apply under 5°C or above 35°C.

### **OBSERVATIONS**

The characteristics of the product can be achieved once it is completely dry and hardened, as well as applied on the specified basis.

The use of the product is theoretical, and it depends on the state of the surface. The real use will be determined for each construction work and its representative tests.

The data explained here is based on our current knowledge, laboratory trials and use in a particular situation with subjective opinions.

Due to the impossibility of establishing an appropriate type and state description of each surface, it is impossible to guarantee the total reproduction for a specific use.

The manufacturer and the seller do not assume, except for specific written agreements, any responsibility coming from the use of our products, results, damage, etc., that can be presented in applications carried out according to our recommendations, since they are out of control of the company.

### **STABILITY AND PRESERVATION IN THE CONTAINER**

Preserve in a well-closed container, under cover and in a temperature between 5-30 °C.

The shelf life of the product in its original container and without opening is two years.

### **SAFETY AND ENVIRONMENT**

Special safety measures are not required since it is a water-based product, except for the usual measures. Do not eat. Keep open containers away from children. Keep a good ventilation in case of an indoor application. For more information, see the safety datasheet of the product.

Data indicated in this technical datasheet can be modified without prior notice.

**REVIEW: 04/04/2024**

PINTURAS IRIS COLOR, S.L –CIF: B02485654 – POL. IND. “EL SALVADOR II” CALLE X, Nº16  
02630-LA RODA (ALBACETE) – APDO. CORREOS 88 - TL: 967 11 42 72 – FAX: 967 44 06 78  
E-mail: [pinturasiriscolor@pinturasiriscolor.com](mailto:pinturasiriscolor@pinturasiriscolor.com) – Web: [pinturasiriscolor.es](http://pinturasiriscolor.es)

PINTURAS IRIS COLOR, S.L –CIF: B02485654 – POL. IND. “EL SALVADOR II” CALLE X, Nº16  
02630-LA RODA (ALBACETE) – APDO. CORREOS 88 - TL: 967 11 42 72 – FAX: 967 44 06 78  
E-mail: [pinturasiriscolor@pinturasiriscolor.com](mailto:pinturasiriscolor@pinturasiriscolor.com) – Web: pinturasiriscolor.es