

Code: 00380

Previous revision: 24/04/2023 Version: 3 Revision: 24/04/2023 Date of printing: 24/04/2023

According to Article 31 of Regulation (EC) No. 1907/2006 (REACH), a safety data sheet (SDS) must be provided for dangerous substances or mixtures. This product does not meet the classification criteria of Regulation (EC) No. 1272/2008 (CLP). Therefore, this document is outside the scope of Article 31 of REACH and the requirements regarding the content of each section are not applicable

SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

PRODUCT IDENTIFIER:

ANTIGOTERAS TERMICO BLANCO

Code: 00380

RELEVANT IDENTIFIED USES OF THE SUBSTANCE OR MIXTURE AND USES ADVISED AGAINST: 1.2

Sectors of use:

Consumer uses (SU21).

Uses advised against:

None. As there is not classified as dangerous, this product can be used in ways other than the identified uses, but all uses have to be consistent with the safety guidelines provided.

Restrictions on manufacture, placing on market and use, according to Annex XVII of Regulation (EC) No. 1907/2006:

Not restricted.

DETAILS OF THE SUPPLIER OF THE SAFETY DATA SHEET: 1.3

PINTURAS IRIS COLOR, S.I.

Avda. III Naves 14-15 - Polígono Industrial El Salvador - 02630 LA RODA (Albacete) ESPAÑA

Phone number: (+34) 967 114272 - Fax: (+34) 967 440678 - www.pinturasiriscolor.es

- E-mail address of the person responsible for the Safety Data Sheet:

pinturasiriscolor@pinturasiriscolor.com

EMERGENCY TELEPHONE NUMBER:

(+34) 967 114272 9:00-14:00 / 16:00-19:00 h

SECTION 2 : HAZARDS IDENTIFICATION

CLASSIFICATION OF THE SUBSTANCE OR MIXTURE: 2.1

This product is not classified as dangerous, in accordance with Regulation (EU) No. 1272/2008~2021/849 (CLP).

Note: This product does not require a Safety Data Sheet according to the Regulation (EC) no. 2020/878. When used as recommended or under ordinary conditions, it should not present a physicochemical, health safety or environmental hazard. However, an MSDS can be provided as a courtesy in response to a customer request.

2.2

This product does not require pictograms, in accordance with Regulation (EU) No. 1272/2008~2021/849 (CLP).

Hazard statements:

None

EUH208

1.4

- Precautionary statements:

Keep out of reach of children.

- Supplementary statements:

and 2-methyl-2H-isothiazol-3-one [EC 220-239-6] (3:1). May produce an allergic reaction.

Contains 1,2-benzisothiazol-3(2H)-one, Reaction mass of 5-chloro-2-methyl-2H-isothiazolin-3-one [EC 247-500-7]

- Substances that contribute to classification:

None in a percentage equal to or higher than the limit for the name.

OTHER HAZARDS: 2.3

Hazards which do not result in classification but which may contribute to the overall hazards of the mixture:

- Other physicochemical hazards:

No other relevant adverse effects are known.

Other adverse human health effects:

Prolonged exposure to vapours may produce transient drowsiness. Prolonged contact may cause skin dryness.

- Other negative environmental effects:

Does not contain substances that fulfil the PBT/vPvB criteria.

Endocrine disrupting properties:

This product does not contain substances with endocrine disrupting properties identified or under evaluation.



Code: 00380

Previous revision: 24/04/2023 Version: 3 Revision: 24/04/2023 Date of printing: 24/04/2023

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

SUBSTANCES 3.1

Not applicable (mixture).

MIXTURES: 3.2

This product is a mixture.

Chemical description:

Mixture of pigments, extenders, resins and additives in aqueous media.

HAZARDOUS INGREDIENTS:

Substances taking part in a percentage higher than the exemption limit:

1 < C < 2 %

Butylglycol acetate

CAS: 112-07-2, EC: 203-933-3, REACH: 01-2119475112-47

CLP: Warning: Acute Tox. (inh.) 4:H332 | Acute Tox. (skin) 4:H312 | Acute

Tox. (oral) 4:H302

C < 0,01 %

1,2-benzisothiazol-3(2H)-one CAS: 2634-33-5, EC: 220-120-9

CLP: Danger: Acute Tox. (oral) 4:H302 (ATE=567 mg/kg) | Skin Irrit. 2:H315 |

Eye Dam. 1:H318 | Skin Sens. 1:H317 | Aquatic Acute 1:H400

C < 0,0015 %

Reaction mass of 5-chloro-2-methyl-2H-isothiazolin-3-one [EC 247-500-7]

and 2-methyl-2H-isothiazol-3-one [EC 220-239-6] (3:1) CAS: 55965-84-9, EC: 611-341-5

CLP: Danger: Acute Tox. (inh.) 2:H330 | Acute Tox. (skin) 2:H310 | Acute Tox. (oral) 3:H301 | Skin Corr. 1C:H314 | Eye Dam. 1:H318 | Áquatic Acute 1:H400 (M=100) | Aquatic Chronic 1:H410 (M=100) | EUH071 | Skin Sens.

1A:H317 (Note B)

Skin Corr. 1C, H314: Skin Irrit. 2, H315:

REACH

CLP00

ATP13

 $0.06 \% \le C < 0.6 \%$ Eye Dam. 1, H318: C ≥0,6 % Eye Irrit. 2, H319: 0,06 % ≤ C < 0,6 % Skin Sens. 1A, H317:

Skin Sens. 1, H317: C ≥0,05 %

C ≥0,0015 %

Impurities:

Does not contain other components or impurities which will influence the classification of the product.

Stabilizers:

None.

Reference to other sections:

For more information, see sections 8, 11, 12 and 16.

SUBSTANCES OF VERY HIGH CONCERN (SVHC):

List updated by ECHA on 17/01/2023.

Substances SVHC subject to authorisation, included in Annex XIV of Regulation (EC) no. 1907/2006:

None.

Substances SVHC candidate to be included in Annex XIV of Regulation (EC) no. 1907/2006:

PERSISTENT, BIOACCUMULABLE AND TOXIC PBT, OR VERY PERSISTENT AND VERY BIOACCUMULABLE VPVB **SUBSTANCES:**

Does not contain substances that fulfil the PBT/vPvB criteria.

SECTION 4: FIRST AID MEASURES

4.1 DESCRIPTION OF FIRST AID MEASURES



Symptoms may occur after exposure, so that in case of direct exposure to the product, when in doubt, or when symptoms persist, seek medical attention. Never give anything by mouth to an unconscious person.

Symptoms and effects, acute and delayed	Description of first-aid measures
It is not expected that symptoms will occur under normal conditions of use.	Should there be any symptoms, transfer the person affected to the open air.
Prolonged contact may cause skin dryness.	Remove contaminated clothing.Wash thoroughly the affected area with plenty of cold or lukewarm water and neutral soap, or use a suitable skin cleanser.
Contact with the eyes produces redness and pain.	Remove contact lenses.Rinse eyes copiously by irrigation with plenty of clean, fresh water, holding the eyelids apart.If irritation persists, consult a physician.
lf swallowed in high doses, may cause gastrointestinal disturbances.	Do not induce vomiting, due to the risk of aspiration.Keep the patient at rest.
	It is not expected that symptoms will occur under normal conditions of use. Prolonged contact may cause skin dryness. Contact with the eyes produces redness and pain. If swallowed in high doses, may cause

4.2

The main symptoms and effects are indicated in sections 4.1 and 11.1

INDICATION OF ANY IMMEDIATE MEDICAL ATTENTION AND SPECIAL TREATMENT NEEDED: 4.3

Notes to physician:

Treatment should be directed at the control of symptoms and the clinical condition of the patient...

Antidotes and contraindications:

Specific antidote not known.

CLP 2.6.4.3.



ANTIGOTERAS TERMICO BLANCO

Code: 00380

Previous revision: 24/04/2023 Version: 3 Revision: 24/04/2023 Date of printing: 24/04/2023

SECTION 5: FIREFIGHTING MEASURES

EXTINGUISHING MEDIA:)

Extinguishing powder or CO2

SPECIAL HAZARDS ARISING FROM THE SUBSTANCE OR MIXTURE: 5.2

As consequence of combustion or thermal decomposition, hazardous products may be produced: carbon monoxide, Carbon dioxide, nitrogen oxides, sulfur oxides, halogenated compounds, hydrochloric acid. Exposure to combustion or decomposition products may be a

ADVICE FOR FIREFIGHTERS: 5.3

Special protective equipment:

Depending on magnitude of fire, heat-proof protective clothing may be required, appropriate independent breathing apparatus, gloves, protective glasses or face masks and boots. If the fire-proof protective equipment is not available or is not being used, combat fire from a sheltered position or from a safe distance. The standard EN469 provides a basic level of protection for chemical incidents.

Cool with water the tanks, cisterns or containers close to sources of heat or fire. Bear in mind the direction of the wind. Do not allow firefighting residue to enter drains, sewers or water courses.

SECTION 6: ACCIDENTAL RELEASE MEASURES

PERSONAL PRECAUTIONS, PROTECTIVE EQUIPMENT AND EMERGENCY PROCEDURES:

Eliminate possible sources of ignition and when appropriate, ventilate the area. Do not smoke. Avoid direct contact with this product. Avoid breathing vapours. Keep people without protection in opposition to the wind direction.

ENVIRONMENTAL PRECAUTIONS: 6.2

Avoid contamination of drains, surface or subterranean water and soil. In the case of large scale spills or when the product contaminates lakes, rivers or sewages, inform the appropriate authorities in accordance with local regulations.

METHODS AND MATERIAL FOR CONTAINMENT AND CLEANING UP: 6.3

Contain and mop up spills with non-combustible absorbent materials (earth, sand, vermiculite, diatomaceous earth, etc..). Keep the remains in a closed container.

REFERENCE TO OTHER SECTIONS: 6.4

For contact information in case of emergency, see section 1.

For information on safe handling, see section 7.

For exposure controls and personal protection measures, see section 8.

For waste disposal, follow the recommendations in section 13.

SECTION 7: HANDLING AND STORAGE

PRECAUTIONS FOR SAFE HANDLING: 7.1

Comply with the existing legislation on health and safety at work.

General recommendations:

Avoid any type of leakage or escape. Keep the container tightly closed.

- Recommendations for the prevention of fire and explosion risks:

Vapours are heavier than air, may spread along floors to a considerable distance, can form explosive mixtures with air and are able to reach distant ignition sources and flame up or explode. Due to its flammability, this material should only be used in areas from which all naked lights and other sources of ignition have been excluded and away from other heat or electrical sources. Switch mobile phones off and do not smoke. No tools with a potential for sparks should be used.

Flashpoint 75* °C (Pensky-Martens) Autoignition temperature:

Not applicable.

- Recommendations for the prevention of toxicological risks:

Do not eat, drink or smoke while handling. After handling, wash hands with soap and water. For exposure controls and personal protection measures, see section 8.

- Recommendations for the prevention of environmental contamination:

It is not considered a danger to the environment. In the case of accidental spillage, follow the instructions indicated in section 6.

CONDITIONS FOR SAFE STORAGE, INCLUDING ANY INCOMPATIBILITIES: 7.2

Forbid the entry to unauthorized persons. Keep out of reach of children. This product should be stored isolated from heat and electrical sources. Do not smoke in storage area. If possible, avoid direct contact with sunlight. In order to avoid leakages, the containers, after use, should be closed carefully and placed in a vertical position. For more information, see section 10.

- Class of store:

According to current legislation.

- Maximum storage period:

24 Months.

- Temperature interval:

min:5 °C, max:40 °C (recommended).

Incompatible materials:

Keep away from oxidizing agents, acids, alkalis.

- Type of packaging:

According to current legislation.

Limit quantity (Seveso III): Directive 2012/18/EU:

Not applicable (product for non industrial use).

SPECIFIC END USE(S): 7.3

For the use of this product particular recommendations apart from that already indicated are not available.



Code: 00380

Version: 3 Revision: 24/04/2023 Previous revision: 24/04/2023 Date of printing: 24/04/2023

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1 CONTROL PARAMETERS:

If a product contains ingredients with exposure limits, may be necessary a personnel monitoring, work place or biological, to determine the effectiveness of the ventilation or other control measures and/or the necessity to use respiratory protective equipment. Reference should be made to EN689, EN14042 and EN482 standard concerning methods for assessing the exposure by inhalation to chemical agents, and exposure to chemical and biological agents. Reference should be also made to national guidance documents for methods for the determination of dangerous substances.

- OCCUPATIONAL EXPOSURE LIMIT VALUES (WEL)

						
EH40/2005 WELs (United	Year	WEL-TWA		WEL-STEL		Remarks
Kingdom) 2018		ppm	mg/m3	ppm	mg/m3	
Butylglycol acetate	2003	20	133	-	-	A3
1,2-benzisothiazol-3(2H)-one	-	-	0,1	-	-	Recommended
Reaction mass of 5-chloro-2-methyl-2H -isothiazolin-3-one [EC 247-500-7] and 2-methyl-2H-isothiazol-3-one [EC 220-239-6] (3:1)	-	-	0,08	-	0,23	Recommended

WEL - Workplace Exposure Limit, TWA - Time Weighted Average (8 hours), STEL - Short Term Exposure Limit (15 min). A3 - Carcinogenic in animals.

- BIOLOGICAL LIMIT VALUES:

Not established

- DERIVED NO-EFFECT LEVEL (DNEL):

Derived no-effect level (DNEL) is a level of exposure that is considered safe, derived from toxicity data according to specific guidances included in REACH. DNEL values may differ from a occupational exposure limit (OEL) for the same chemical. OEL values may come recommended by a particular company, a government regulatory agency or an organization of experts. Although considered protective of health, the OEL values are derived by a process different of REACH.

- DERIVED NO-EFFECT LEVEL, WORKERS:- Systemic effects, acute and chronic:	DNEL Inhalation mg/m3		DNEL Cutaneous mg/kg bw/d		DNEL Oral mg/kg bw/d	
Reaction mass of 5-chloro-2-methyl-2H-isothiazolin-3-one [EC 247-500-7] and 2-methyl-2H-isothiazol-3-one [EC 220-239-6] (3:1)	- (a)	- (c)	- (a)	- (c)	- (a)	- (c)
1,2-benzisothiazol-3(2H)-one	- (a)	- (c)	- (a)	- (c)	- (a)	- (c)
Butylglycol acetate	775 (a)	133 (c)	102 (a)	102 (c)	- (a)	- (c)
- DERIVED NO-EFFECT LEVEL, WORKERS:- Local effects, acute and chronic:	DNEL Inhalation mg/m3		DNEL Cutaneous mg/cm2		DNEL Eyes mg/cm2	
Reaction mass of 5-chloro-2-methyl-2H-isothiazolin-3-one [EC 247-500-7] and 2-methyl-2H-isothiazol-3-one [EC 220-239-6] (3:1)	- (a)	- (c)	- (a)	- (c)	- (a)	- (c)
1,2-benzisothiazol-3(2H)-one	- (a)	- (c)	- (a)	- (c)	- (a)	- (c)
Butylglycol acetate	333 (a)	s/r (c)	s/r (a)	s/r (c)	- (a)	- (c)
- DERIVED NO-EFFECT LEVEL, GENERAL POPULATION:- Systemic effects, acute and chronic:	DNEL Inhalation mg/m3		DNEL Cutaneous mg/kg bw/d		DNEL Eyes mg/kg bw/d	
Reaction mass of 5-chloro-2-methyl-2H-isothiazolin-3-one [EC 247-500-7] and 2-methyl-2H-isothiazol-3-one [EC 220-239-6] (3:1)	- (a)	- (c)	- (a)	- (c)	- (a)	- (c)
1,2-benzisothiazol-3(2H)-one	- (a)	- (c)	- (a)	- (c)	- (a)	- (c)
Butylglycol acetate	499 (a)	67 (c)	27 (a)	36 (c)	18 (a)	4,3 (c)
- LOCAL EFFECTS, ACUTE AND CHRONIC:- Local effects, acute and chronic:	DNEL Inhalation mg/m3		DNEL Cutaneous mg/cm2		DNEL Eyes mg/cm2	
Reaction mass of 5-chloro-2-methyl-2H-isothiazolin-3-one [EC 247-500-7] and 2-methyl-2H-isothiazol-3-one [EC 220-239-6] (3:1)	- (a)	- (c)	- (a)	- (c)	- (a)	- (c)
1,2-benzisothiazol-3(2H)-one	- (a)	- (c)	- (a)	- (c)	- (a)	- (c)
Butylglycol acetate	166 (a)	s/r (c)	s/r (a)	s/r (c)	- (a)	- (c)

- (a) Acute, short-term exposure, (c) Chronic, long-term or repeated exposure.
- (-) DNEL not available (without data of registration REACH).
- s/r DNEL not derived (not identified hazard).

- PREDICTED NO-EFFECT CONCENTRATION (PNEC):

		
PNEC Fresh water	PNEC Marine	PNEC Intermittent
mg/l	mg/l	mg/l
-	-	-



Code: 00380

Version: 3 Revision: 24/04/2023 Previous revision: 24/04/2023 Date of printing: 24/04/2023

1,2-benzisothiazol-3(2H)-one		-		-		-
Butylglycol acetate		0.304		0.0304		0.56
- WASTEWATER TREATMENT PLANTS (STP)	PNEC STP		PNEC Sediments		PNEC Sediments	
AND SEDIMENTS IN FRESH- AND MARINE	mg/l		mg/kg dw/d		mg/kg dw/d	
<u>WATER:</u>						
Reaction mass of 5-chloro-2-methyl-2H-		-		-		-
isothiazolin-3-one [EC 247-500-7] and 2-						
methyl-2H-isothiazol-3-one [EC 220-239-6]						
(3:1)						
1,2-benzisothiazol-3(2H)-one		-		-		-
Butylglycol acetate		90		2.03		0.203
- PREDICTED NO-EFFECT CONCENTRATION,	PNEC Air		PNEC Soil		PNEC Oral	
TERRESTRIAL ORGANISMS:- Air, soil and	mg/m3		mg/kg dw/d		mg/kg dw/d	
effects for predators and humans:						
Reaction mass of 5-chloro-2-methyl-2H-		-		-		-
isothiazolin-3-one [EC 247-500-7] and 2-						
methyl-2H-isothiazol-3-one [EC 220-239-6]						
(3:1)						
1,2-benzisothiazol-3(2H)-one		-		-		-
Butylglycol acetate		-		0.68		60
() DNEC not available (without data of registrati	ON DEVCHI		<u> </u>			

(-) - PNEC not available (without data of registration REACH).

8.2 EXPOSURE CONTROLS:

ENGINEERING MEASURES:







Provide adequate ventilation. Where reasonably practicable, this should be achieved by the use of local exhaust ventilation and good general extraction. If these measures are not sufficient to maintain concentrations of particulates and vapours below the Occupational Exposure Limits, suitable respiratory protection must be worn.

- Protection of respiratory system:

Avoid the inhalation of vapours.

- Protection of eyes and face:

It is recommended to install water taps or sources with clean water close to the working area.

- Protection of hands and skin:

It is recommended to install water taps or sources with clean water close to the working area.Barrier creams may help to protect the exposed areas of the skin.Barrier creams should not be applied once exposure has occurred.

OCCUPATIONAL EXPOSURE CONTROLS: REGULATION (EU) NO. 2016/425:

As a general measure on prevention and safety in the work place, we recommend the use of a basic personal protection equipment (PPE), with the corresponding marking. For more information on personal protective equipment (storage, use, cleaning, maintenance, type and characteristics of the PPE, protection class, marking, category, CEN norm, etc..), you should consult the informative brochures provided by the manufacturers of PPE.

Mask:	No.
Safety goggles:	Advisable.Clean daily and disinfect at regular intervals in accordance with the instructions of the manufacturer.
Face shield:	No.
Gloves:	Gloves resistant against chemicals (EN374). When repeated or prolonged contact with the product is expected, gloves of protection level 5 or higher should be used, with a breakthrough time of >240 min. When short contact with the product is expected, use gloves with a protection level 2 or higher should be used, with a breakthrough time >30 min. The breakthrough time of the selected glove material should be in accordance with the pretended period of use. There are several factors (for example, temperature), they do in practice the period of use of a protective gloves resistant against chemicals is clearly lower than the established standard EN374. Due to the wide variety of circumstances and possibilities, the instructions/specifications provided by the glove supplier should be taken into account. The gloves should be immediately replaced when any sign of degradation is noted.
Boots:	No.
Apron:	No.
Clothing:	No.

- Thermal hazards:

Not applicable (the product is handled at room temperature).

ENVIRONMENTAL EXPOSURE CONTROLS:

Avoid any spillage in the environment. Avoid any release into the atmosphere.

- Spills on the soil:



Code: 00380

Version: 3 Revision: 24/04/2023 Previous revision: 24/04/2023 Date of printing: 24/04/2023

Prevent contamination of soil.

- Spills in water:

Do not allow to escape into drains, sewers or water courses.

-Water Management Act:

This product does not contain any substance included in the list of priority substances in the field of water policy under Directive 2000/60/EC~2013/39/EU.

- Emissions to the atmosphere:

Because of volatility, emissions to the atmosphere while handling and use may result. Avoid any release into the atmosphere.

VOC (product ready for use*):

It is applicable the Directive 2004/42/EC, on the limitation of emissions of volatile compounds due to the use of organic solvents: PAINTS AND VARNISHES (defined in the Directive 2004/42/EC, Annex I.1): Emission subcategory i) One-pack performance coating, water-borne. VOC (product ready for use*): (ANTIGOTERAS TERMICO BLANCO Cod. 00380 = 100 in volume): 11,7 g/l (VOC max.140 g/l* starting from 01.01.2010)

VOC (industrial installations):

If this product is used in an industrial installation, it must be verified if it is applicable the Directive 2010/75/CE (DL.127/2013, on the limitation of emissions of volatile compounds due to the use of organic solvents in certain activities and installations: Solvents: 2,17 % Weight, VOC (supply): 1,01 % Weight, VOC: 0,61 % C (expressed as carbon), Molecular weight (average): 159,68 , Number C atoms (average): 7,94

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

9.1 <u>INFORMATION ON BASIC PHYSICAL AND CHEMICAL PROPERTIES:</u>

Appearance

Physical state: Paste
Colour: White
Odour: Characteristic

Odour threshold: Not available (mixture).

Change of state

Softening point/range:

Not available (mixture).

Initial boiling point:

> 100* °C at 760 mmHg

- Flammability:

Flashpoint 75* °C (Pensky-Martens) CLP 2.6.4.3.

Lower/upper flammability or explosive limits: Not available Autoignition temperature: Not applicable.

Stability

Decomposition temperature: > 200,00* °C

pH-value

pH: 8,5 ± 1 at 20°C

Viscosity:

Dynamic viscosity: 25000 ± 5000 cps at 20°C Kinematic viscosity: $7450,63^*$ mm2/s at 40°C

Solubility(ies):

Solubility in water Inmiscible

Liposolubility: Not applicable (inorganic product).

Partition coefficient: n-octanol/water: Not applicable (mixture).

- Volatility:

Vapour pressure: 17,4201* mmHg at 20° C Vapour pressure: 12,034* kPa at 50° C Evaporation rate: Not available (lack of data).

Density

Relative density: $1,150 \pm 0,05$ at 20/4°C Relative water

Relative vapour density: Not available.

Particle characteristics

Particle size: Not available.

Explosive properties:

Vapours can form explosive mixtures with air and are able to flame up or explode in presence of an ignition source.

Oxidizing properties:

Not classified as oxidizing product.

*Estimated values based on the substances composing the mixture.

9.2 OTHER INFORMATION:

Information regarding physical hazard classes

No additional information available.

Other security features:

VOC (supply): 1,0 % Weight VOC (supply): 11,7 g/l

Nonvolatile: 68,38 * % Weight 1h. 60°C



Code: 00380

Version: 3 Revision: 24/04/2023 Previous revision: 24/04/2023 Date of printing: 24/04/2023

The values indicated do not always coincide with product specifications. The data for the product specifications can be found in the corresponding technical data sheet. For additional information concerning physical and chemical properties related to safety and environment, see sections 7 and 12.

SECTION 10: STABILITY AND REACTIVITY

10.1 REACTIVITY:

Corrosivity to metals:
 It is not corrosive to metals.

- Pyrophorical properties:

It is not pyrophoric.

10.2 CHEMICAL STABILITY:

Stable under recommended storage and handling conditions.

10.3 POSSIBILITY OF HAZARDOUS REACTIONS:

Possible dangerous reaction with oxidizing agents, acids, alkalis.

10.4 CONDITIONS TO AVOID:

- Heat:

Keep away from sources of heat.

Liaht:

If possible, avoid direct contact with sunlight.

- Air:

The product is not affected by exposure to air, but should not be left the containers open.

Pressure:

Not relevant.

- Shock:

The product is not sensitive to shocks, but as a recommendation of a general nature should be avoided bumps and rough handling to avoid dents and breakage of packaging, especially when the product is handled in large quantities, and during loading and download operations.

10.5 INCOMPATIBLE MATERIALS

Keep away from oxidizing agents, acids, alkalis.

10.6 HAZARDOUS DECOMPOSITION PRODUCTS:

As consequence of thermal decomposition, hazardous products may be produced: nitrogen oxides, sulfur oxides, hydrochloric acid, halogenated compounds.

SECTION 11: TOXICOLOGICAL INFORMATION

No experimental toxicological data on the preparation is available. The toxicological classification for these mixture has been carried out by using the conventional calculation method of the Regulation (EU) No. 1272/2008~2021/849 (CLP).

11.1 INFORMATION ON HAZARD CLASSES AS DEFINED IN REGULATION (EC) NO 1272/2008 :

ACUTE TOXICITY:

Dose and lethal concentrations	DL50 (OECD401)	DL50 (OECD402)	CL50 (OECD403)
for individual ingredients:	mg/kg bw Oral	mg/kg bw Cutaneous	mg/m3·4h Inhalation
Reaction mass of 5-chloro-2-methyl-2H-isothiazolin-3-one [EC 247-500-7] and 2-methyl-2H-isothiazol-3-one [EC 220-239-6] (3:1)	74,9 Rat	140 Rat	> 1230 Rat
1,2-benzisothiazol-3(2H)-one	1020 Rat	> 2000 Rat	> 2050 Rat
Butylglycol acetate	1880 Rat	1480 Rabbit	> 400 Rat
Estimates of acute toxicity (ATE) for individual ingredients:	ATE mg/kg bw Oral	ATE mg/kg bw Cutaneous	ATE mg/m3·4h Inhalation
Reaction mass of 5-chloro-2-methyl-2H-isothiazolin-3-one [EC 247-500-7] and 2-methyl-2H-isothiazol-3-one [EC 220-239-6] (3:1)	74,9	140	*> 50
1,2-benzisothiazol-3(2H)-one	*567	-	-
Butylglycol acetate	1880	*1480	*11000 Vapours

^{(*) -} Point estimates of acute toxicity corresponding to the classification category (see GHS/CLP Table 3.1.2). These values are designed to be used in the calculation of the ATE for classification of a mixture based on its components and do not represent test results.

- No observed adverse effect level

Not available

Lowest observed adverse effect level

Not available

INFORMATION ON LIKELY ROUTES OF EXPOSURE: ACUTE TOXICITY:

Routes of exposure Acute toxicity Cat. Main effects, acute and/or delayed Criteria	I II/OULES OF EXPOSULE	IACUTA TOVICITY	Cat.		Criteria
--	------------------------	-----------------	------	--	----------

^{(-) -} The components that are assumed to have no acute toxicity at the upper threshold of category 4 for the corresponding exposure route are ignored.



Code: 00380

Previous revision: 24/04/2023 Version: 3 Revision: 24/04/2023 Date of printing: 24/04/2023

Inhalation: Not classified	ATE > 20000 mg/m3	- Not classified as a product with acute toxicity if inhaled (based on available data, the classification criteria are not met).
Skin: Not classified	ATE > 5000 mg/kg bw	Not classified as a product with acute toxicity in contact with skin (based on available data, the classification criteria are not met).
Eyes: Not classified	Not available.	Not classified as a product with acute toxicity GHS/CLP by eye contact (lack of data).
Ingestion: Not classified	ATE > 5000 mg/kg bw	Not classified as a product with acute toxicity GHS/CLP if swallowed (based on available data, the classification criteria are not met).

GHS/CLP 3.1.3.6: Classification of mixtures based on ingredients of the mixture (additivity formula).

CORROSION / IRRITATION / SENSITISATION:

Danger class	Target organs	Cat.	Main effects, acute and/or delayed	Criteria
 Respiratory corrosion/irritation Not classified 	: -	-	irritant by inhalation (based on available data	GHS/CLP 1.2.6. 3.8.3.4.
- Skin corrosion/irritation: Not classified		-	· ·	GHS/CLP 3.2.3.3.
 Serious eye damage/irritation: Not classified 		-	· ·	GHS/CLP 3.3.3.3.
- Respiratory sensitisation: Not classified	-	-	1 3 7	GHS/CLP 3.4.3.3.
- Skin sensitisation: Not classified	-	-	Not classified as a product sensitising by skin contact (based on available data, the classification criteria are not met).	GHS/CLP 3.4.3.3.

GHS/CLP 3.2.3.3: Classification of the mixture when data are available for all components or only for some components. GHS/CLP 3.3.3.3: Classification of the mixture when data are available for all components or only for some components. GHS/CLP 3.4.3.3: Classification of the mixture when data are available for all components or only for some components. GHS/CLP 3.8.3.4: Classification of the mixture when data are available for all components or only for some components.

- ASPIRATION HAZARD:

Danger class	Target organs	Cat.	Main effects, acute and/or delayed	Criteria
- Aspiration hazard: Not classified	_		'	GHS/CLP 3.10.3.3.

GHS/CLP 3.10.3.3: Classification of the mixture when data are available for all components or only for some components.

SPECIFIC TARGET ORGANS TOXICITY (STOT): Single exposure (SE) and/or Repeated exposure (RE):

Not classified as a dangerous product for target organs.

GHS/CLP 3.8.3.4: Classification of the mixture when data are available for all components or only for some components.

CMR EFFECTS:

- Carcinogenic effects:

It is not considered as a carcinogenic product.

- Genotoxicity:

It is not considered as a mutagenic product.

- Toxicity for reproduction:

Does not harm fertility. Does not harm the unborn child.

Effects via lactation:

Not classified as a hazardous product for children breast-fed.

DELAYED AND IMMEDIATE EFFECTS AS WELL AS CHRONIC EFFECTS FROM SHORT AND LONG-TERM EXPOSURE:

Routes of exposure

May be absorbed by inhalation of vapour, through the skin and by ingestion.

- Short-term exposure:



Code: 00380

Version: 3 Revision: 24/04/2023 Previous revision: 24/04/2023 Date of printing: 24/04/2023

Exposure to solvent vapour concentrations in excess of the stated occupational exposure limit, may result in adverse health effects, such as mucous membrane and respiratory system irritation and adverse effects on kidneys, liver and central nervous system. Liquid splashes in the eyes may cause irritation and reversible damage. If swallowed, may cause irritation of the throat; other effects may be the same as described in the exposure to vapours.

- Long-term or repeated exposure:

Repeated or prolonged contact may cause removal of natural fat from the skin, resulting in non-allergic contact dermatitis and absorption through the skin.

INTERACTIVE EFFECTS:

Not available.

INFORMATION ABOUT TOXICOCINETICS, METABOLISM AND DISTRIBUTION:

- Dermal absorption:

This preparation contains the following substances for which dermal absorption can be very high: Butylglycol acetate

- Basic toxicokinetics:

Not available.

ADDITIONAL INFORMATION:

This preparation contains glycols that are readily absorbed through the skin and may cause harmful effects on the blood.

11.2 INFORMATION ON OTHER HAZARDS:

Endocrine disrupting properties:

This product does not contain substances with endocrine disrupting properties identified or under evaluation.

Other information:

No additional information available.

SECTION 12: ECOLOGICAL INFORMATION

No experimental ecotoxicological data on the preparation as such is available. The ecotoxicological classification for these mixture has been carried out by using the conventional calculation method of the Regulation (EU) No. 1272/2008~2021/849 (CLP).

12.1 TOXICITY:

- Acute toxicity in aquatic environment for individual ingredients	CL50 (OECD 203) mg/l-96hours	CE50 (OECD 202) mg/l·48hours	CE50 (OECD 201) mg/l·72hours
Reaction mass of 5-chloro-2-methyl-2H-isothiazolin-3-one [EC 247-500-7] and 2-methyl-2H-isothiazol-3-one [EC 220-239-6] (3:1)	0.19 - Fishes	0.16 - Daphniae	0.037 - Algae
1,2-benzisothiazol-3(2H)-one	1.2 - Fishes	0.85 - Daphniae	0.37 - Algae
Butylglycol acetate	28 - Fishes	37 - Daphniae	1570 - Algae

- No observed effect concentration	NOEC (OECD 210) mg/l · 28 days	NOEC (OECD 211)	NOEC (OECD 201)
Reaction mass of 5-chloro-2-methyl-2H-isothiazolin-3-one [EC 247-500-7] and 2-methyl-2H-isothiazol-3-one [EC 220-239-6] (3:1)	0.02 - Fishes	0.011 - Daphniae	0.004 - Algae

Lowest observed effect concentration

Not available

ASSESSMENT OF AQUATIC TOXICITY:

Aquatic toxicity	Cat.	Main hazards to the aquatic environment	Criteria
- Acute aquatic toxicity: Not classified	-	1	GHS/CLP 4.1.3.5.5.3.
- Chronic aquatic toxicity:	-	Not classified as a dangerous product with chronic toxicity to aquatic life with long lasting effects (based on available data, the classification criteria are not met).	GHS/CLP 4.1.3.5.5.4.

CLP 4.1.3.5.5.3: Classification of a mixture for acute hazards, based on summation of classified components.

CLP 4.1.3.5.5.4: Classification of a mixture for chronic (long term) hazards, based on summation of classified components.

12.2 PERSISTENCE AND DEGRADABILITY:

- Biodegradability:

Not available.

Aerobic biodegradation	COD	%DBO/DQO	Biodegradabilidad
for individual ingredients	mgO2/g	5 days 14 days 28 days	



ANTIGOTERAS TERMICO BLANCO Code: 00380 Previous revision: 24/04/2023 Version: 3 Revision: 24/04/2023 Date of printing: 24/04/2023 Reaction mass of 5-chloro-2-methyl-2H-55 Not easy isothiazolin-3-one [EC 247-500-7] and 2methyl-2H-isothiazol-3-one [EC 220-239-6] (3:1)1,2-benzisothiazol-3(2H)-one Not easy 51 71 88 Butylglycol acetate 2071 Easy Note: Biodegradability data correspond to an average of data from various bibliographic sources. - Hydrolysis: Not available. - Photodegradability: Not available **BIOACCUMULATIVE POTENTIAL:** 12.3 Not available logPow Bioaccumulation **BCF** Potential L/kg for individual ingredients Reaction mass of 5-chloro-2-methyl-2H-0.75 3.2 (calculated) Unlikely, low isothiazolin-3-one [EC 247-500-7] and 2methyl-2H-isothiazol-3-one [EC 220-239-6] (3:1)1,2-benzisothiazol-3(2H)-one 0.64 3.2 (calculated) Unlikely, low Butylglycol acetate 1.51 5.1 (calculated) No bioaccumulable MOBILITY IN SOIL: 12.4 Not available Mobility log Poc Constant of Henry Potential Pa·m3/mol 20°C for individual ingredients Reaction mass of 5-chloro-2-methyl-2H-0,45 Unlikely, low isothiazolin-3-one [EC 247-500-7] and 2methyl-2H-isothiazol-3-one [EC 220-239-6] (3:1)1,2-benzisothiazol-3(2H)-one 1,05 Unlikely, low Butylglycol acetate 1.41 0.32 (calculated) No bioaccumulable ESULTS OF PBT AND VPVB ASSESMENT:(Annex XIII of Regulation (EC) no. 12.5 Does not contain substances that fulfil the PBT/vPvB criteria. 12.6 ENDOCRINE DISRUPTING PROPERTIES This product does not contain substances with endocrine disrupting properties identified or under evaluation. OTHER ADVERSE EFFECTS: 12.7 Ozone depletion potential: Not available.

- Photochemical ozone creation potential:

Not available.

- Earth global warming potential:

In case of fire or incineration liberates CO2.

SECTION 13: DISPOSAL CONSIDERATIONS

WASTE TREATMENT METHODS: Directive 2008/98/EC~Regulation (EU) no. 1357/2014: 13.1

Take all necessary measures to prevent the production of waste whenever possible. Analyse possible methods for revaluation or recycling. Do not discharge into drains or the environment, dispose at an authorised waste collection point. Waste should be handled and disposed in accordance with current local and national regulations. For exposure controls and personal protection measures, see section 8.

Disposal of empty containers: Directive 94/62/EC~2015/720/EU, Decision 2000/532/EC~2014/955/EU:

Emptied containers and packaging should be disposed in accordance with currently local and national regulations. The classification of packaging as hazardous waste will depend on the degree of empting of the same, being the holder of the residue responsible for their classification, in accordance with Chapter 15 01 of Decision 2000/532/EC, and forwarding to the appropriate final destination. With contaminated containers and packaging, adopt the same measures as for the product in itself.

Procedures for neutralising or destroying the product:

Controlled incineration in special facilities for chemical waste, in accordance with local regulations.

(Language:EN)



ANTIGOTERAS TERMICO BLANCO

Code: 00380

Version	: 3 Revision: 24/04/2023	Previous revision: 24/04/2023	Date of printing: 24/04/2023
SECTION	I 14: TRANSPORT INFORMATION		
14.1	UN NUMBER OR ID NUMBER:		
	Not applicable		
14.2	UN PROPER SHIPPING NAME:		
	Not applicable		
14.3	TRANSPORT HAZARD CLASS(ES):		
	Transport by road (ADR 2021) and		
	Transport by rail (RID 2021):		
	No reglamented		
	Transport by sea (IMDG 39-18):		
	No reglamented		
	Transport by air (ICAO/IATA 2021):		
	No reglamented		
	Transport by inland waterways (ADN):		
	No reglamented		
14.4	PACKING GROUP:		
	No reglamented		
14.5	ENVIRONMENTAL HAZARDS:		
	Not applicable (not classified as hazardous for the envi	ronment).	
14.6	SPECIAL PRECAUTIONS FOR USER:		
	Ensure that persons transporting the product know who	at to do in case of accident or spill. Always transport i	n closed containers that are
44.7	upright and secure. Ensure adequate ventilation. MARITIME TRANSPORT IN BULK ACCORDING	TO IMO INCIDI IMENTO.	
14.7	Not applicable.	TO IMO INSTRUMENTS.	
CECTION	I 15: REGULATORY INFORMATION		
		HI ATIONS // FOICH ATION OPENIES FOR THE	CURCTANCE OR MIXTURE.
15.1	SAFETY, HEALTH AND ENVIRONMENTAL REG		SUBSTANCE OR MIXTURE:
	The regulations applicable to this product generally are Restrictions on manufacture, placing on market an		
	See section 1.2	ld use.	
	Tactile warning of danger:		
	Not applicable (the classification criteria are not met).		
	Child safety protection:		
	Not applicable (the classification criteria are not met).		
	VOC information on the label:		
	Contains VOC max. 11,7 g/l for the product ready for us	se - The limit value 2004/42/EC-IIA cat. i) One-pack r	performance coating, water-
	borne. is VOC max. 140 g/l (2010)	···· , -··· , -··· , -··· , -··· , -··· , -··· , -··· , -··· , -··· , -··· ,	,
	OTHER REGULATIONS:		
	Not available.		
	Control of the risks inherent in major accidents (Se	eveso III):	
	See section 7.2		
	Other local legislations:		
	The receiver should verify the possible existence of loc	al regulations applicable to the chemical.	
15.2	CHEMICAL SAFETY ASSESSMENT:		
	A chemical safety assessment has not been carried ou	t for this mixture.	

In accordance with Regulation (EC) No. 1907/2006 and Regulation (EU) No. 2020/878



ANTIGOTERAS TERMICO BLANCO

Code: 00380

Version: 3 Revision: 24/04/2023 Previous revision: 24/04/2023 Date of printing: 24/04/2023

SECTION 16: OTHER INFORMATION

16.1 TEXT OF THE PHRASES AND NOTES REFERENCED IN SECTIONS 2 AND/OR 3:

Hazard statements according the Regulation (EU) No. 1272/2008~2021/849 (CLP), Annex III:

H301 Toxic if swallowed. H302 Harmful if swallowed. H310 Fatal in contact with skin. H312 Harmful in contact with skin. H314 Causes severe skin burns and eye damage. H315 Causes skin irritation. H317 May cause an allergic skin reaction. H318 Causes serious eye damage. H330 Fatal if inhaled. H332 Harmful if inhaled. H400 Very toxic to aquatic life. H410 Very toxic to aquatic life with long lasting effects. EUH071 Corrosive to the respiratory tract.

Notes related to the identification, classification and labelling of the substances or mixtures:

Note B: Some substances (acids, bases, etc.) are placed on the market in aqueous solutions at various concentrations and, therefore, these solutions require different classification and labelling since the hazards vary at different concentrations. In Part 3 entries with Note B have a general designation of the following type: 'nitric acid ... %'. In this case the supplier must state the percentage concentration of the solution on the label. Unless otherwise stated, it is assumed that the percentage concentration is calculated on a weight/weight basis.

EVALUATION OF THE INFORMATION ON THE DANGER OF MIXTURES:

See sections 9.1, 11.1 and 12.1.

ADVICES ON ANY TRAINING APPROPRIATE FOR WORKERS:

It is recommended for all staff that will handle this product to carry out a basic training in occupational risk and prevention, in order to provide understanding and interpretation of Safety Data Sheets and labelling of products as well.

MAIN LITERATURE REFERENCES AND SOURCES FOR DATA:

- · European Chemicals Agency: ECHA, http://echa.europa.eu/
- · Access to European Union Law, http://eur-lex.europa.eu/
- Industrial Solvents Handbook, Ibert Mellan (Noyes Data Co., 1970).
- · Threshold Limit Values, (AGCIH, 2021).
- · European agreement on the international carriage of dangerous goods by road, (ADR 2021).
- International Maritime Dangerous Goods Code IMDG including Amendment 39-18 (IMO, 2018).

ABBREVIATIONS AND ACRONYMS:

List of abbreviations and acronyms that can be used (but not necessarily used) in this Safety Data Sheet:

- · REACH: Regulation concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals.
- · GHS: Globally Harmonized System of Classification and Labelling of Chemicals of the United Nations.
- · CLP: European regularion on Classificatin, Labelling amd Packaging of substances and chemical mixtures.
- · EINECS: European Inventory of Existing Commercial Chemical Substances.
- · ELINCS: European List of Notified Chemical Substances.
- · CAS: Chemical Abstracts Service (Division of the American Chemical Society).
- $\cdot \ \mathsf{UVCB:} \ \mathsf{Substances} \ \mathsf{of} \ \mathsf{Unknown} \ \mathsf{or} \ \mathsf{Variable} \ \mathsf{composition}, \ \mathsf{complex} \ \mathsf{reaction} \ \mathsf{products} \ \mathsf{or} \ \mathsf{biological} \ \mathsf{materials}.$
- · SVHC: Substances of Very High Concern.
- \cdot PBT: Persistent, bioaccumulable and toxic substances.
- · vPvB: Very persistent and very bioaccumulable substances.
- · VOC: Volatile Organic Compounds.
- · DNEL: Derived No-Effect Level (REACH).
- · PNEC: Predicted No-Effect Concentration (REACH).
- · LC50: Lethal concentration, 50 percent.
- · LD50: Lethal dose, 50 percent.
- · UN: United Nations Organisation.
- $\cdot \, \text{ADR: European agreement concerning the international carriage of dangeous goods by road.}$
- · RID: Regulations concerning the international transport of dangeous goods by rail.
- · IMDG: International Maritime code for Dangerous Goods.
- · IATA: International Air Transport Association.
- · ICAO: International Civil Aviation Organization.

SAFETY DATA SHEET REGULATIONS:

Safety Data Sheet in accordance with Article 31 of Regulation (EC) No. 1907/2006 (REACH) and Annex of Regulation (EU) No. 2020/878.

 HISTORIC:
 REVISION:

 Version: 2
 03/02/2020

 Version: 3
 24/04/2023

Changes since previous Safety Data Sheet:

Legislative, contextual, numerical, methodological and normative changes since the previous version of the present Safety Data Sheet are identified by #.

The information of this Safety Data Sheet, is based on the present state of knowledge and on current UE and national laws, as the users" working conditions beyond our knowledge and control. The product is not to be used for other purposes than those specified, without first obtaining written handling instruction. It is always the responsibility of the user to take all necessary steps in order to fulfil the demand laid down in the local rules and legislation. The information in this Safety Data Sheet is meant as a description of the safety requirements of the product and it is not to be considered as a guarantee of the product"s properties.