



## TECHNICAL DATASHEET

# CONSOLIDATING WATER-REPELLENT PRIMER

Aqueous primer for inorganic materials

### **DESCRIPTION**

Consolidating water-repellent fluid for water-based construction and insulating materials. It does not create a film once it is dry.

### **RECOMMENDED USE**

To consolidate construction materials (concrete, stone, sandstone, tiles, bricks, clay, etc.) and insulating materials (perlite, vermiculite and aerated concrete) that have been degraded because of bad weather, due to its alkalinity resistance and absorption. It is used as an aqueous primer for façades before using paints, coatings in order to avoid humidity and equalise the absorption of the material. It is also used for already painted surfaces when they are worn away, like plaster or plastic paints in order to consolidate them to provide water-repellent characteristics. It is not advisable on non-absorbent or porous surfaces.

### **CHARACTERISTICS**

- . Slight consolidating and water-repellent.
- . It does not change the colour of the material.
- . Quick-drying and hardening. No stickiness.
- . Protection from humidity.
- . Slight wet appearance, reviving the surface.
- . Excellent water-steam permeability. Water and humidity resistant.
- . It increases the thermal efficacy of the coating.
- . It avoids salts and efflorescence, extending the shelf life of the product.
- . It reduces dirt. High self-cleaning ability.
- . Water-repellent but it allows water steam diffusion and CO<sub>2</sub>.

### **TECHNICAL CHARACTERISTICS**

Main component:	Acrylic/siloxane copolymer in aqueous solution.
Appearance:	Transparent.
Diluent:	Water.
Solids by weight:	6 ± 1 %
Specific weight:	1,0 + 0,05 g/ml
Colour:	Colourless.
Drying:	15-30 minutes.
Repainting:	Moist over moist.
Theoretical yield:	0,5-8,0 m <sup>2</sup> /l and coat depending on the absorption of the material.
Packaging:	1 L, 5 L and 20 L.



## TECHNICAL DATASHEET

# CONSOLIDATING WATER-REPELLENT PRIMER

**Aqueous primer for inorganic materials**

### **APPLICATION**

#### **Surface preparation:**

On cement, concrete, if the surface is new, the application must wait minimum 28 days to make sure the concrete or cement is completely dry. Later, wash with a hydrochloric acid solution at 10 % in water and rinse with water. Let it dry before applying the product. In any case, the surface must be clean and free of any dust, grease or anything that could affect the adhesion between the pavement and the product.

To paint other surfaces not specified in this Technical Datasheet, consult our Technical Department.

#### **Instructions:**

Stir the content until it is uniform. Do not dilute the product. It can be applied with brush, roller or by pulverisation or immersion. It is advisable to apply a layer saturating the surface and then a second coat when the first coat has been absorbed but without waiting to be dry (moist over moist). Before applying the product, windows, crystals, etc. must be covered in all those surfaces that are not absorbent, since the product dries quickly and once it is dry, it is impossible to remove the stains.

Never apply under 5°C or above 35°C or when rain, high humidity, mist, frost, etc. are expected.

### **OBSERVATIONS**

The characteristics of the product can be achieved once it is completely dry and hardened, as well as applied on the specified basis.

The use of the product is theoretical, and it depends on the state of the surface. The real use will be determined for each construction work and its representative tests.

The data explained here is based on our current knowledge, laboratory trials and use in a particular situation with subjective opinions.

Due to the impossibility of establishing an appropriate type and state description of each surface, it is impossible to guarantee the total reproduction for a specific use.

The manufacturer and the seller do not assume, except for specific written agreements, any responsibility coming from the use of our products, results, damage, etc., that can be presented in applications carried out according to our recommendations, since they are out of control of the company.

### **STABILITY AND PRESERVATION IN THE CONTAINER**

Preserve in a well-closed container, under cover and in a temperature between 5-30 °C.

The shelf life of the product in its original container and without opening is two years.

### **SAFETY AND ENVIRONMENT**

Special safety measures are not required since it is a water-based product, except for the usual measures. Do not eat. Keep open containers away from children. Keep a good ventilation in case of an indoor application. For more information, see the safety datasheet of the product.

Data indicated in this technical datasheet can be modified without prior notice.

**REVIEW: 04/04/2024**