



DATA SHEET

IRIS CHALK PAINT CHALK

EFFECT WATER-BASED PAINT

DESCRIPTION

Very matt water-based chalk effect paint for the restoration and decoration of furniture and other surfaces, creating vintage-aged or stripped-off effects.

RECOMMENDED USES

Suitable as a high decoration product in DIY work, handicrafts, restoration and crafts on wood, concrete, plaster, plaster, etc. Recommended for indoor use.

PROPERTIES

- . Adequate resistance and adhesion.
- . Quick drying.
- . Sandable.
- . Very matte look and feel.
- . Great filling power.
- . No smell.
- . Cleaning with water.

TECHNICAL FEATURES

Vehicle: Acrylic polymer in aqueous dispersion.

Pigments: Titanium dioxide and selected fillers.

Appearance: Matte.

Diluent: Water.

Solids by weight: $68 \pm 2\%$

Specific Weight: $1.49 + 0.05$ g/ml

VOCs (2010): Maximum 30 g/l.

Color: White. Other colors please consult.

Drying: 30 minutes.

Repainting: Minimum 4 hours.

Theoretical Yield: 6 - 8 m²/l per hand.

Packaging: 750 ml



SHEET

IRIS CHALK PAINT CHALK

EFFECT WATER-BASED PAINT

APPLICATION

Surface preparation: On new surfaces made of wood, plaster, cement, stone, porous ceramics, clean the surface to remove traces of dust, grease and dirt in general and apply a first coat diluted between 10-15% with water as a primer. Then apply one or two more less diluted coats, depending on your taste. When applied to wood, it is recommended to apply in accordance with the grain.

How to use: Stir the contents of the container well until the product is perfectly homogenized. Spread evenly in a generous layer and without over-reviewing. It is recommended to apply two to three coats. It can be applied with an air spray gun, brush or short hair roller.

Never apply below 5°C or above 35°C and always with R.H. <80%.

Decapé effect: With this method, you can create beautiful distressed effects. To do this, we will apply two or three coats of IRIS CHALK PAINT in the two or three pastel colors that we like the most, respecting the repainting times.

- Stripping effect with sandpaper: Two or three coats of IRIS CHALK PAINT are applied and gently worn away with sandpaper. Do not wear in a general way, but in those points that you want to highlight until the color of the other layers appears.
- Wax stripping effect: Apply one or two coats of IRIS CHALK PAINT and let dry. Then apply a layer of natural wax to the spots where you want to give the effect. Then apply another coat of IRIS CHALK PAINT in a color that contrasts with the one used in the base. Once the layers have dried, the last layer of IRIS CHALK PAINT will easily pop off where the wax was applied, generating a peeling effect.

Vintage Effect: Apply two or three coats, allowing to dry properly. Once the paint is dry, with a green scouring pad or sandpaper, gently rub the entire surface. You have to exert more pressure on corners and edges, apart from the points you want to highlight. This friction generates dust that needs to be removed. In this way, an aged appearance has been given to the surface.

REMARKS

The characteristics of the product are obtained once it has been completely dried and cross-linked, as well as applied to the specified substrates

Consumption is theoretical and depends on the state of the support. The actual consumption should be determined for each particular work by means of representative tests.

The data reviewed here are based on our current knowledge, laboratory tests and their practical use in specific circumstances through subjective judgments.

Due to the impossibility of establishing an appropriate description for each nature and condition of each surface, it is impossible for us to guarantee total reproducibility in each specific use.

Unless otherwise specifically agreed in writing, both the manufacturer and the seller do not assume any liability arising from the use of our products, for the results, damages, etc., that may arise in applications made in accordance with our recommendations, as these are beyond the control of the company.

SHELF LIFE AND SHELF LIFE

Store the container tightly closed, indoors and at a temperature between 5 and 30°C

The shelf life of the product in its original, unopened packaging is two years.

SAFETY & ENVIRONMENT

No special safety measures are required as it is a water-based product, except for the usual ones. Do not ingest the product. Keep open canisters out of the reach of children. Maintain good ventilation in case of indoor application. For more information, see the product's safety data sheet.

The data indicated in this data sheet may be changed without prior notice.

REVISION: 04/04/2024