



## TECHNICAL DATASHEET

# STIPPLED-FINISH EFFECT PAINT

Paste

### DESCRIPTION

Economic paste for the decoration of walls and ceilings for indoors.

### RECOMMENDED USES

Paint for all types of masonry surfaces (plaster, stucco, cement, etc.), interior decoration, plasterboard panels and all types of construction materials, when desired to achieve a low cost. Adequate to get stippled-finish, graining, texturised effect. Wall and ceiling decoration for indoors on any type of masonry material, in new or old building sites, when desired to achieve good value for money.

### CHARACTERISTICS

- . Made of different types of calcium carbonates and sulphates with a fine grain size and extraordinary whiteness.
- . Great resistance, hardness and adhesion.
- . Matt.
- . Excellent performance.
- . Low cost.
- . Silky appearance and touch.
- . Good brush stroke, coverage and performance.
- . Excellent value for money.
- . Totally breathable.
- . It can be dyed with universal or water-based dyes.

### TECHNICAL CHARACTERISTICS

Pigments:	Calcium carbonate and calcium sulphate.
Appearance:	Matt.
Paint thinner:	Water.
Specific weight:	1,70 ± 0,05 gr/cc
Colour:	White.
Drying:	5 hours to 20°C.
Repainting:	Minimum 8 hours.
Theoretical performance:	1,5 m <sup>2</sup> /Kg and coat. Depending on the chosen effect.
Packaging:	22 Kg.



## TECHNICAL DATASHEET

# STIPPLED-FINISH EFFECT PAINT

Paste

### **APPLICATION**

#### **Surface preparation:**

On new surfaces of construction materials, it is advisable to check if their state is adequate. Clean the surface to remove any dust remains, grease and general dirt.

On already painted surfaces with plastic paint, this one will have to be removed. In case of dealing with distemper paste, proceed like if it were a new surface. If it has good adhesion, sand it softly to tinge and remove the dust before painting.

In case of efflorescence or salty residue, treat it with any neutralizer liquid or any solution with hydrochloric acid to 10 % in water, clear with plenty of water and let it dry before painting.

In case of pollution due to mold, fungus, algae or other elements, apply a water and bleach solution or hydrochloric acid to 10 % on the surface and let it work between 15-20 min. Next, clear with plenty of water and let it dry completely before applying the paint. Proceed like if it were a new surface or an already painted surface.

For other surfaces not contemplated in this technical datasheet, contact our Technical Department.

#### **Instructions for use:**

Stir the content until it is uniform. Always apply on clean, dry surfaces without any dust, wax, grease, etc.

Apply a first diluted coat with brush, roller or spray gun, diluting the paste with water to obtain the appropriate viscosity, acting as a base for the decorative effect that is going to be applied afterwards. Once it is dry, the chosen effect can be applied, without diluting the paste and using the most appropriate method. Never apply under 5°C or above 35°C.

### **OBSERVATIONS**

The characteristics of the product can be achieved once it is completely dry and hardened, as well as applied on the specified basis.

Consumption is theoretical and it depends on the state of the material. The real consumption will be determined for each construction work and its representative tests.

The data explained here is based on our current knowledge, laboratory trials and use in a particular circumstance with subjective opinions.

Due to the impossibility of establishing an appropriate description to each nature and state of each surface, it is impossible to guarantee the total reproduction for each specific use.

The manufacturer and the seller do not assume, except for specific written agreements, any responsibility coming from the use of our products, results, damage, etc., that can be presented in applications carried out according to our recommendations, since they are out of control of the company.

### **STABILITY AND PRESERVATION IN THE CONTAINER**

Preserve in a well-closed container, under cover and in a temperature between 5-30 °C.

The shelf life of the product in its original container and without opening is two years.

### **SAFETY AND ENVIRONMENT**

Special safety measures are not required since it is a product with a water base, except for the usual ones. Do not eat. Keep open containers away from children. Keep a good ventilation in case of an indoors application. For more information, see the safety datasheet of the product.

Data indicated in this technical datasheet can be modified without prior notice.

REVIEW: 04/04/2024