



DATA SHEET

WHITE STAIN REMOVER

Anti-stain spray

DESCRIPTION

Paint formulated for use as a base coat for the insulation of stains on walls, fumes, greases, moisture, nicotine and other products.

RECOMMENDED USES

Suitable for indoor and outdoor use, and on surfaces such as concrete, plaster, stone, cement, and others. It can also be used as a white background layer on:

- . DIY.
- . Industry.
- . Crafts.
- . Domestic.

INSTRUCTIONS FOR USE

- . Shake the spray very well before use, about a minute after hearing the noise of the mixer.
- . Apply in thin layers for best results, three thin coats is always better than one thick, repaintable after five minutes with the same paint.
- . Invert the spray to purge the valve after use, if the diffuser gets clogged, replace it with a new one.
- . Do not apply to connected equipment and use in well-ventilated areas.
- . Ask for safety data sheets.

CHARACTERISTICS

- . Quick drying.
- . Good adhesion.
- . Excellent covering power.
- . It does not contain lead or other heavy metals.
- . High color fastness. It does not yellow.
- . Easy to apply and repaint.

Ambient T min 8°C / T surface between 5-50 °C/H.R. max 85 %

Características físicas		Características envasado	
Tipo ligante	Acrílico termoplástico	Capacidad nominal	400 ml
Color	Blanco	Resistencia del envase al calor	< 50°C
Brillo	<10%		
Secado al tacto	5 minutos	Propelente	BP
Secado total	15 minutos		
Espesor de capa seca	20 µm por capa (2 capas)		
Packaging Characteristics	Binder Type		
400 ml	Colour		
<	Brightness 2 años		
Repintado	Dry to the touch		
BP	Total drying		
Condiciones de aplicación	Dry Layer Thickness		

The data indicated in this data sheet may be changed without prior notice.

REVISION: 04/04/2024