



# TECHNICAL DATASHEET **FIBRE COLOURPLAST**

**Ready-to-use filler with fibreglass**

## **DESCRIPTION**

Elastic and ready-to-use filler with fibreglass to fill crevices and small holes in all type of masonry surfaces.

## **RECOMMENDED USES**

- It covers and fills small fissures and holes.
- Apply directly on interior materials, as long as they are hard, dry and clean.
- Wood, plaster or stucco surfaces with imperfections and irregularities.

## **CHARACTERISTICS**

- Easy application, smoothing and sanding.
- It avoids difficult fissures and holes reappearance.
- Filling and sealing fissures and crevices.
- If after applying it, there are still imperfections, it can be applied again after 2-8 hours approx.
- Once the surface is sanded, this one shows great whiteness, hardness and a soft touch.
- It can be applied with trowel without any effort.

## **TECHNICAL CHARACTERISTICS**

Resistance to scratches:	2B (pencil hardness)
pH:	Neutral
Adhesion:	> 0,5 MPa
Drying (25°C/50% humidity):	2-8 hours/mm
Performance:	1,75 m <sup>2</sup> /Kg
Packaging:	1 Kg.

## **APPLICATION**

### **Surface preparation:**

The material must be clean and not humid. Materials with a dusty nature must be consolidated with a binder, preferably with an acrylic binder, like our BINDER, since dust stops adhesion between materials. Also, old materials made of dead plaster or parts poorly adhered must be repaired. It is not advisable to restore old materials without repairing them previously. If they present any cavity or hole, they must be scratched and removed. After this process, a binder must be applied to remove any dust remains.

### **Instructions for use:**

- 1) In order to fill holes, it is advisable to use a medium-size trowel that allows pressuring the mixture to the inside of the hole. If it is possible, use a trowel bigger than the size of the hole.
- 2) In order to cover crevices and fissures, it is advisable to clean and prepare the surfaces on both sides of the fissure or crevice.
- 3) When the material is dry, proceed to sand it and apply plaster horizontally from right to left, and splices from left to right.
- 4) At last, after letting it dry, apply a second coat, sand it and if there are no imperfections, proceed to paint it.



# TECHNICAL DATASHEET

## FIBRE COLOURPLAST

Ready-to-use filler with fibreglass

### **OBSERVATIONS**

The characteristics of the product can be achieved once it is completely dry and hardened, as well as applied on the specified basis.

**Use the product during its shelf life. If not, the result may cause unfavourable characteristics.**

**Do not mix with any other material, since it will not preserve its technical characteristics.**

**Do not apply on non-absorbent materials. It can be repainted with most of traditional plastic paints, but in case of doubt, test it first.**

**Do not get the material wet before applying it.**

Consumption is theoretical and it depends on the state of the material. The real consumption will be determined for each construction work and its representative tests.

The data explained here is based on our current knowledge, laboratory trials and use in a particular circumstance with subjective opinions.

Due to the impossibility of establishing an appropriate description to each nature and state of each surface, it is impossible to guarantee the total reproduction for each specific use.

The manufacturer and the seller do not assume, except for specific written agreements, any responsibility coming from the use of our products, results, damage, etc., that can be presented in applications carried out according to our recommendations, since they are out of control of the company.

### **STABILITY AND PRESERVATION IN THE CONTAINER**

Preserve in a well-closed container, under cover and in a temperature between 5-30 °C.

The shelf life of the product in its original container and without opening is two years.

### **SAFETY AND ENVIRONMENT**

Special safety measures are not required, except for the usual ones. Do not eat. Do not vomit. Keep open containers away from children. Keep a good ventilation in case of an indoors application. Use a face mask in case of use for a long period of time. In case of contact with skin, wash with water and soap or an appropriate cleanser. For more information, see the safety datasheet of the product.

Data indicated in this technical datasheet can be modified without prior notice.

**REVIEW: 04/04/2024**