



#### **DESCRIPTION**

Matt plastic paint with high coverage. For indoors and outdoors.

#### **RECOMMENDED USE**

Matt plastic paint for all types of masonry surfaces (plaster, stucco, cement, fibre cement, etc.) due to its resistance and absorption it is specially used for façades, restoration, exterior and interior decoration, plasterboard panels and all construction materials.

#### **CHARACTERISTICS**

- . Good resistance, hardness and adhesion.
- . High yield.
- . Impermeable and breathable.
- . Excellent wet scrub resistance after 7 days from its application.
- . Bad weather resistant.
- . Silky appearance and touch.
- . Protection from humidity.
- . Good brush stroke, coverage and yield.
- . Minimum retraction when drying.
- . It does not turn yellow.

#### **TECHNICAL CHARACTERISTICS**

Main component:	Vinyl copolymer in aqueous dispersion.
Pigments:	Titanium dioxide and additives.
Appearance:	Silky matt.
Diluent:	Water.
Solids by weight:	65 ± 2 %
Specific weight:	1,59 ± 0,05 g/ml
Volatile organic compounds (2010):	26 g/l (max. 40 g/l since 01.01.2010). According to the Directive 2004/42/EC of the European Parliament.
Colour:	White. For other colours, please consult us.
Drying:	30-60 minutes.
Repainting:	Minimum 6 hours.
Theoretical yield:	8-10 m <sup>2</sup> /l and coat. Depending on the irregularity and absorption of the surface.
Packaging:	4 L and 14 L.



#### APPLICATION

##### **Surface preparation:**

On new construction material surfaces, it is advisable to check if their state is adequate. Clean the surface to remove any dust remains, grease and general dirt and apply the first coat diluted between 10-15 % with water. In order to consolidate or unify the absorption, it is recommendable to use an acrylic binder like our BINDER to achieve a better result.

On already painted surfaces, if the paint is in a bad state, it must be removed. In case of dealing with distemper paste, proceed like if it were a new surface. If it has good adhesion, sand it softly to tinge and remove the dust before painting.

In case of efflorescence or salty residue, treat it with any neutralizer liquid and rinse with plenty of water and let it dry before painting.

In case of pollution due to mould, fungus, algae or other elements, apply a water and bleach solution or hydrochloric acid at 10 % on the surface and leave it for approximately 15-20 min. Next, rinse with plenty of water and let it dry completely before applying the paint. Proceed like if it were a new surface or an already painted surface.

##### **Instructions:**

Stir the content until it is uniform. Always apply on clean, dry surfaces without any dust, wax, grease, etc. It can be applied with brush, roller or spray gun. For brush and roller application, apply the first coat diluted between 10-15 % with water and the second one diluted lightly. For spray gun application, dilute it between 5-10 %.

Never apply under 5°C or above 35°C.

#### OBSERVATIONS

The characteristics of the product can be achieved once it is completely dry and hardened, as well as applied on the specified basis.

The use of the product is theoretical, and it depends on the state of the surface. The real use will be determined for each construction work and its representative tests.

The data explained here is based on our current knowledge, laboratory trials and use in a particular situation with subjective opinions.

Due to the impossibility of establishing an appropriate type and state description of each surface, it is impossible to guarantee the total reproduction for a specific use.

The manufacturer and the seller do not assume, except for specific written agreements, any responsibility coming from the use of our products, results, damage, etc., that can be presented in applications carried out according to our recommendations, since they are out of control of the company.

#### STABILITY AND PRESERVATION IN THE CONTAINER

Preserve in a well-closed container, under cover and in a temperature between 5-30 °C.

The shelf life of the product in its original container and without opening is two years.

#### SAFETY AND ENVIRONMENT

Special safety measures are not required since it is a water-based product, except for the usual measures. Do not eat. Keep open containers away from children. Keep a good ventilation in case of an indoor application. For more information, see the safety datasheet of the product.

Data indicated in this technical datasheet can be modified without prior notice.

**REVIEW: 04/04/2024**